

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An endodontic device for detecting moisture within a root canal, comprising:
 - an endodontic cone formed of a water absorptive material; and
 - a moisture sensitive and pH insensitive chemical indicator comprising at least one cobalt salt applied to the water absorptive material that changes color when moistened with water regardless of the pH of the water.
2. (Original) An endodontic device as recited in claim 1, wherein the water absorptive material comprises paper.
3. (Original) An endodontic device as recited in claim 1, wherein the cobalt salt comprises at least one of cobalt fluoride, cobalt iodide, and cobalt sulfate.
4. (Original) An endodontic device as recited in claim 1, wherein the cobalt salt comprises cobalt chloride.
5. (Original) An endodontic device as recited in claim 1, wherein the chemical indicator further changes to a different color to indicate the presence of sodium hypochlorite.
6. (Original) An endodontic device as recited in claim 1, wherein the endodontic device is initially blue but changes to pink when moistened with water.
7. (Original) An endodontic device as recited in claim 1, wherein the endodontic device is initially blue but changes to black when moistened with aqueous sodium hypochlorite.

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

8. (Original) An endodontic device for detecting moisture and aqueous sodium hypochlorite within a root canal, comprising:

an endodontic cone formed of a water absorptive material; and

a moisture and sodium hypochlorite sensitive chemical indicator comprising at least one cobalt salt applied to the water absorptive material that changes to a first color when moistened with water and a second color when moistened with aqueous sodium hypochlorite.

9. (Original) An endodontic device as recited in claim 8, wherein the cobalt salt comprises cobalt chloride.

10. (Original) An endodontic device as recited in claim 8, wherein the device is initially blue when dry and changes to pink when moistened with water and to black when moistened with aqueous sodium hypochlorite.

11. (Currently Amended) An endodontic device for detecting moisture within a root canal, comprising:

an endodontic cone formed of a water absorptive material;

a pH changing material applied to the water absorptive material; and

a pH sensitive color changing indicator applied to the water absorptive material;

and

wherein the endodontic device changes color when moistened with water,

wherein the pH changing material enhances a change in color of the endodontic device when the endodontic cone is moistened with water compared to a change in color of an endodontic device without the pH changing material.

12. (Original) An endodontic device as recited in claim 11, wherein the pH changing material comprises an alkali metal oxide, alkali metal hydroxide, alkali metal carbonate, alkaline earth metal oxide, or alkaline earth metal hydroxide.

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

13. (Original) An endodontic device as recited in claim 12, wherein the pH changing material comprises at least one of CaO, KOH, and K₂CO₃.

14. (Original) An endodontic device as recited in claim 12, wherein the pH sensitive color changing indicator comprises phenolphthalein.

15. (Original) An endodontic device as recited in claim 11, wherein the pH changing material comprises citric acid.

16. (Currently Amended) A method of manufacturing an endodontic device for detecting moisture within a root canal, comprising the steps of:

providing an endodontic cone comprising a water absorptive material;

applying an aqueous solution that includes (i) at least one of a wetting agent or surfactant and (ii) a moisture sensitive color-changing chemical indicator comprising at least one cobalt salt to the endodontic cone; and

drying the endodontic cone so as to be substantially free of moisture.

17. (Original) A method of manufacturing a device as recited in claim 16, wherein the endodontic cone is dried using an oven.

18. (Cancelled)

19. (Currently Amended) A method of manufacturing a device as recited in claim 16 [[18]], wherein the wetting agent comprises ethyl alcohol.

20. (Currently Amended) A method of manufacturing a device as recited in claim 16 [[18]], wherein the wetting agent is present in the aqueous solution in an amount up to about 10%.

21. (Currently Amended) A method of manufacturing a device as recited in claim 16 [[18]], wherein the surfactant is present in the aqueous solution in an amount up to about 1%.

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

22. (Original) A method of manufacturing a device as recited in claim 16, wherein the cobalt salt is present in the aqueous solution in an amount between about 0.5% and about 50% by weight.

23. (Original) A method of manufacturing a device as recited in claim 16, wherein the cobalt salt is present in the aqueous solution in an amount between about 5% and about 40% by weight.

24. (Original) A method of manufacturing a device as recited in claim 16, wherein the cobalt salt is present in the aqueous solution in an amount between about 10% and about 30% by weight.

25. (Original) A method of manufacturing an endodontic device for detecting moisture within a root canal, comprising the steps of:

- providing an endodontic cone comprising a water absorptive material;
- applying a pH changing solution that includes a pH changing material to the endodontic cone;
- drying the endodontic cone so as to be substantially free of moisture;
- applying an anhydrous pH sensitive indicator solution that includes a pH sensitive color changing indicator and an anhydrous volatile solvent to the endodontic cone;
- drying the endodontic cone so as to be substantially dry.

26. (Original) A method of manufacturing a device as recited in claim 25, wherein the endodontic cone is dried using an oven.

27. (Original) A method of manufacturing a device as recited in claim 25, wherein the pH changing material is present in the pH changing solution in an amount between about 0.01% and about 0.5% by weight.

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

28. (Original) A method of manufacturing a device as recited in claim 25, wherein the pH sensitive color changing indicator is present in the anhydrous pH sensitive indicator solution in an amount between about 0.01% and about 0.5%.

29. (Original) A method of manufacturing a device as recited in claim 25, wherein the anhydrous volatile solvent comprises one of isopropanol and ethanol.

30. (Currently Amended) A method of using a device for detecting moisture within a root canal, comprising the steps of:

inserting an endodontic device as recited in claim ~~[[1]]~~ 8 within a root canal of a patient's tooth;

withdrawing the device and observing whether the chemical indicator has changed color, indicating the presence of moisture within the root canal.

31. (Currently Amended) A method of using a device as recited in claim 30, further comprising observing whether the chemical indicator has changed to a color that indicates the presence of ~~wherein the endodontic device changes to a first color when moistened with water and to a second color when moistened with~~ aqueous sodium hypochlorite.

32. (Original) A method of using a device for detecting moisture within a root canal, comprising the steps of:

inserting an endodontic device as recited in claim 11 within a root canal of a patient's tooth;

withdrawing the device and observing whether the chemical indicator has changed color, indicating the presence of moisture within the root canal.

Application No. 10/718,755
Amendment "A" dated June 13, 2005
Reply to Office Action mailed May 4, 2005

33. (New) A method of manufacturing an endodontic device for detecting moisture within a root canal, comprising the steps of:

providing an endodontic cone comprising a water absorptive material;

applying an aqueous solution that includes a moisture sensitive color-changing chemical indicator comprising at least one cobalt salt to the endodontic cone; and

drying the endodontic cone using an oven so as to be substantially free of moisture.